

FRT610 Fingerprint Scanner

Small size fingerprint reader



Lightweight. Accurate. Reliable. The ARATEK FRT610 Fingerprint Scanner is designed for demanding conditions that require portability and accuracy. Using advanced fingerprint capture technology, FRT610 is the logical choice for identification and authentication applications across many industries such as finance, health care, and hospitality.

The ARATEK FRT610 is compliant with international standards including ISO and ANSI, guarantee high quality output at all times.

Features

International Standard

ISO19794-2, ISO19794-4, ANSI 378, ANSI 381 and WSQ supported

High Image Quality

Capacitive fingerprint technology with superior image quality

Strong Adaption

Good adaption for dry, moist and rough fingerprints

Correction and Authentication

Support auto correction and 360 degree rotation authentication

Cloud Platform

Seamlessly join in Aratek TrustLinkTM biometrics authentication platform

OS Support

Windows2000, XP, Vista, Windows7 / 8 / 10, Android and other embedded systems

SDK

Comprehensive software development kit is available for development and integration

Applications

- PC/Network Security
- Hospitality
- Finance and Banking

- Telecommunication
- Healthcare
- Law Enforcement

FRT610 Fingerprint Scanner

Physical Parameter

Dimension	100*50*15mm (L*W*H)
-----------	---------------------

Performance Parameter

Capture Mode	Capacitive Touch
Platen Size	11.4*15.3 mm
Sensing Area	10.4*14.4 mm
Fingerprint Image Size	256*288 pixels
Image Resolution	508 dpi
Gray level	256 level



Operation Environment

Work Voltage	5.0 V (USB power supply)
Work Current	≤50 mA
Temperature	0°C~55°C
Humidity	20~90%R.H
ESD	Contact: ±6KV Air: ±8KV

Supported OS

Windows XP / 7 / 8 / 10, Android, Linux





Aratek Biometrics Technology Co., Ltd

10F, No. 131, Songjiang Road, Zhongshan District, Taipei City 10491, Taiwan

Tel: +886 2-2501-0001 E-mail: sales@aratek.co Web: www.aratek.co