

MC310 THE DIRECT-TO-CARD PRINTER

Designed to perfectly fit into any card issuance environment, the new Matica MC310 directto-card printer offers a superior print quality and a complete line of encoding, lamination and communication options. Its versatility provides a solution to all vertical markets which need to run card issuance programs that require reliable and consistent high quality printing, converting the MC310 into the most flexible and reliable card printer platform in the market.

Reliable and easy-to-use, the Matica MC310 offers high-performance color card printing. Available as a single side, the MC310 can easily evolve to dual-side printing, anytime, anywhere without the need to install additional hardware components.

The 4 LED status indicators on the front of the printer, in combination with the 2-line LCD display, facilitates the use of the printer providing all necessary information to the operator, making the MC310 extremely easy to use.

Optional in-line magnetic stripe encoder and dual interface encoders for contact/contactless smart cards, maximizes its functionality for a broader set of application uses, such as access control, time & attendance, payment services and many more.

The MC310 is accompanied with a comprehensive ribbon program to cover all issuance needs in all vertical markets, including the new Matica YMCScKO ribbon to increase the

number of visual security elements (VSE) on the card for security applications.

Need more durable and secure cards? The use of the optional, easy-to-install, in-line MC-L2 lamination module in combination with the MC310 allows to issue cards which last more and have additional level of security against counterfeit.

The MC310 direct-to-card printer is notably fast with an output of over 180 cards per hour when printing color single side and up to 850 cph when printing in monochrome.

- Color dye-sublimation 300 dpi resolution
- Up to 180 color cards per hour
- Optional lamination module
- Reliable and easy-to-use
- On demand printing or batch processes
- 4 Years Warranty

DIRECT-TO-CARD

PRINTFR

MC310

MATICA

THE DIRECT-TO-CARD PRINTER

TECHNICAL SPECIFICATIONS

| Print method | Dye-sublimation direct-to-card |
|----------------------------|---|
| Print Resolution | 300 x 300 dpi |
| Print area | Edge-to-edge (CR-80 cards) |
| Print mode | Dual side (optional) |
| Print speed | 180 cph (YMCKO single side, batch) ⁽¹⁾ |
| | 850 cph (monochrome printing) ⁽¹⁾ |
| Card Thickness | 0.25 mm - 1.25 mm (10 mil - 50 mil) |
| Card Types | CR-80 PVC, PVC-C, Re-writable cards |
| Input Hopper Capacity | 100 cards (0.76 mm - 30 mil thickness) |
| Output Hopper Capacity | 30 cards (front) / 80 cards (rear) |
| Exception feeding | Included |
| User Interface | Two-lines x 16 chars LCD display |
| | 4 x LED status indicator |
| Encoding Options | Magnetic stripe encoder ISO7811 |
| | Dual interface smart card encoder |
| Other Options | Matica MC-L2 laminator |
| Communications Interface | USB 2.0 Ethernet 10BaseT, 100BaseT |
| | WiFi 802.11 a/b/g (optional) |
| chromXpert® Ribbon Program | YMCKO (250 prints) |
| | YMCKO-K (200 prints) |
| | YMCKO-KO (200 prints) |
| | 1/2 YMC-KO (400 prints) |
| | 1/2 YMCKO-KO (250 prints) |
| | YMCScKO (200 prints) |
| | KO (800 prints) |
| | Monochrome (2000 prints) |
| | (K, Silver, Gold, White, Red, Green, Blue) |
| | Scratch-off (2000 prints) |
| <u></u> | |

| Smart Ribbon Protection | Ribbon automatic recognition |
|--------------------------------|---|
| | RFID (13.56 MHz) TAG |
| | Two-level encoding potection |
| Memory | 128 Mbytes |
| Safety | Support for Kensington® security lock |
| Operating Systems | Windows© driver (32/64 bits) |
| | XP, SP3, Vista, W7, W8, W10 |
| Integration Tools | SDK available for system integrators |
| | EDIsecure [®] middleware |
| Warranty | 4 years ⁽²⁾ |
| Printer Dimensions (H x W x D) | 255,6 x 202 x 405,4 mm |
| | (10.6" x 7.9" x 15.9") |
| Weight | 10 kg. (22 lbs) |
| Power Supply | 220-240V/110-115V, 50-60 Hz |
| Operating Environment | Temperature: 15°C - 40°C (59°F - 104°F) |
| | Humidity: 20% - 65% (non-condensing) |
| Storage Conditions | Temperature: -5°C to -70°C (23°F - 158° |
| | Humidity: 20% - 70% (non-condensing) |
| Quality Standards | - RoHs |
| | - CE, FCC, CQC, UL, WEEE |
| | - Proposition 65 (California, USA) |
| | - Standby mode and reduced power consumption |
| | - Sound pressure less than 48 dB (A) in operation mode (ISO 7779) |

MC3IO

⁽¹⁾Using native Matica Windows® Driver ⁽²⁾Warranty subjected to the use of chromXpert® Ribbons



- Corporate cards

- Access control cards
- Campus / student cards
- Customer / loyalty cards
- Government cards

Authorized Reseller / System Integrator

